



- Proven Wertheim quality
- Resistance grade III
- Light fire protection

Privately insurable up to EUR 200.000

Commercial insurable

up to EUR 100.000

EN1143-1 Burglary protection



Grade III



Grade III



4102 (light fire protection)



Class EN 3

Product Information

Door Hinge

DIN right - standard optional: DIN left

Door Opening Angle

180°

Body

Double-walled, reinforced, filled with armored highly resistant filler material

Door Structure

Triple-walled, reinforced, filled with armored highly resistant filler material, internal boltwork with partial drill protection

Locking

Boltwork with large steel bolts, protected by an additional emergency locking mechanism, continuous profile on the hinge side

Anchoring

Prepared for floor and rear wall bolting, anchoring material included in the scope of delivery optional: additional holes (position according to customer requirements)

Cable Hole

Door hinge side, rear wall top optional: additional holes (position according to customer requirements)

IAS Connection

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS)

Colour

Grey: RAL 7037 optional: paint finish according to RAL

Locks

Key lock VdS class 2, S&G, 2 keys (140 mm) Electronic lock VdS class 2, Wittkopp Primor 2600 optional: other lock models (main locks or possible additional locks)

Interior

Adjustable shelf optional: additional shelf, inside locker, drawer, pull-out shelf

Accessories

Optional: VdS-approved steel plinth, fire protection door rebate seal, IAS switch set, interior lighting





Model Overview

CM Series



Model	CM15	CM20	CM25	CM30	CM35	CM40
Ext. dimensions h×w×d (mm) incl. hinges and handle	595×575×495	765×575×495	935×575×495	1105×735×555	1275×735×555	1445×735×555
Int. dimensions h×w×d (mm)	515×495×310	685×495×310	855×495×310	1025×655×370	1195×655×370	1365×655×370
Shelves Standard	1	1	2	2	3	3
Volume (l)	79	105	131	248	290	331
Weight* (appr. kg)	280	335	390	565	635	705

In addition to the indicated outer depth of the safe, a further 6 mm must be taken into account for the Primor electronic lock variant. *The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.