



- Proven Wertheim quality
- Resistance grade III
- Certified fire protection

# **Privately insurable** up to EUR 200.000

# **Commercial insurable**

up to EUR 100.000



EN1143-1 Burglary protection



Grade III



Grade III + LFS30





Class EN 3

# **Product Information**

## **Door Hinge**

DIN right - standard optional: DIN left

# **Door Opening Angle**

180°

#### **Body**

Double-walled, reinforced, filled with armored highly resistant filler and heat-absorbing materials

#### **Door Structure**

Triple-walled with double rebate, reinforced, filled with armored highly resistant filler and heat-absorbing materials, internal boltwork with partial drill protection, door rebate with several fire and smoke protection seals

### Locking

boltwork with large steel bolts, protected by an additional emergency locking mechanism, continuous profile on the hinge side

# Anchoring

Prepared for floor and rear wall bolting, anchoring material included in the scope of delivery

#### Cable Hole

Door hinge side, rear wall bottom

#### **IAS Connection**

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS)

#### Colour

Grey: RAL 7037 optional: paint finish according to RAL

#### Locks

Key lock VdS class 2, S&G, 2 keys (165 mm) Electronic lock VdS class 2, Wittkopp Primor 2600 optional: other lock models (main locks or possible additional locks)

#### Interior

Adjustable shelf optional: additional shelf, inside locker, drawer, pull-out shelf

#### Accessories

Optional: IAS switch set, interior lighting





# **Model Overview**

# **CP Series**



Model	CP15	CP20	CP25	CP30	CP35	CP40
Ext. dimensions h×w×d (mm) incl. hinges and handle	629×605×522	799×605×522	969×605×522	1139×605×522	1309×605×522	1479×605×522
Int. dimensions h×w×d (mm)	515×495×310	685×495×310	855×495×310	1025×495×310	1195×495×310	1365×495×310
<b>Shelves</b> Standard	1	1	2	2	3	3
Volume (l)	79	105	131	157	183	209
<b>Weight*</b> (appr. kg)	295	350	410	465	520	575

In addition to the indicated outer depth of the safe, a further 6 mm must be taken into account for the Primor electronic lock variant. \*The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.