

Swing-in Door Safes

CWP Series



Proven Wertheim quality

Interior: lockable drawer, 2 pull-out shelves

- Resistance grade III
- Light fire protection
- Space saving swing in doors

Privately insurable	Commercial insurable
up to EUR 200.000	up to EUR 100.000



EN1143-1 Burglary protection



Grade III



Grade III



4102 (light fire protection)



Class EN 3

Product Information

Door Hinge

DIN right

Models CWP0652 | CWP0902 double-doored

Door Opening

Swing-in-doors – the doors swing into the side of the safe body when opened, leaving the space in front of the safe completely free. Several safes can be placed next to each other without the open doors obstructing each other.

Body

Triple-walled, reinforced, filled with armored highly resistant filler material

Door Structure

Triple-walled, reinforced, with armored highly resistant filler material, internal boltwork with partial drill protection

Locking

Three-way moving boltwork with large steel bolts, protected by an additional emergency locking mechanism, continuous profile on the hinge side

Anchoring

Prepared for floor bolting, anchoring material included in the scope of delivery optional: additional holes (position according to customer requirements)

Cable Hole

In the rear wall

optional: additional holes

IAS Connection

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS)

Colour

Grey: RAL 7037

optional: paint finish according to RAL

Locks

Key lock VdS class 2, Secu, 2 keys (125 mm) Electronic lock VdS class 2, dormakaba Combi B 90 optional: other lock models (main locks or possible additional locks)

Interior

Optional: drawer (lockable), pull-out shelf

Accessories

Optional: IAS switch set, interior lighting

Option

Multisafe version – certified to VdS 2450 Grade III (SE105301)

Model Overview

Model	Ext. dimensions h×w×d (mm)	Int. dimensions h×w×d (mm)	Volume (l)	Weight* (approx. kg)
CWP0651	648×850×754	486×514×590	147	515
CWP0901	878×850×754	716×514×590	217	635
CWP0652	648×1308×754	486×820×590	235	730
CWP0902	878×1308×754	716×820×590	346	890

In addition to the indicated outer depth of the safe, a further 20 mm must be taken into account for fittings.

*The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.